



LIST OF MODULES

- 3 x square tower
- 1 x hexagonal tower
- 3 x hipped roof
- 1 x roof
- 1 x suspended bridge
- 1 x balancing beam
- 1 x tunnel
- 1 x rope netrance
- 1 x arc shaped entrance
- 1 x entry ladder
- 2 x climbing entrance
- 1 x slide
- 1 x steel dexterous unit
- 1 x rope lattice
- 2 x rope chimney
- 1 x TIC TAC TOE
- 2 x barrier W4 Z2
- 3 x barrier W6 Z

TECHNICAL DATA

- Max. height fall 2,0 m
- Dimensions 10,37 x 7,01 x 4,00 m
- Safety area 13,7 x 9,9 m
- Safety area dimensions 94,1 m²
- Recommended safety surface According to norm 1176-1:2017

Available options:

	STANDARD	PREMIUM
WOOD	construction elements made of solid wood, impregnated surface ,with square profile 95 x 95 mm	construction elements made of glued-laminated timber, impregnated surface, with square profile 95 x 95 mm
STEEL	galvanized and powder-coated steel elements	galvanized and powder-coated steel elements
PLATES	HPL sheets	HPL and three-coat HDPE panels with milled drawings
SLIDES	stainless steel slide with side-guard panels made of HDPE sheets	stainless steel slide with side-guard panels made of HDPE sheets and three-coat HDPE panels with milled drawings
FOUNDATIONS	The device permanently sited in the ground with C16 / 20 class concrete	The device permanently sited in the ground with C16 / 20 class concrete
ROPES	ropes made of steel cores wrapped in polypropylene strings, joined by nylon or aluminum connectors	ropes made of steel cores wrapped in polypropylene strings, joined by nylon or aluminum connectors
CHAINS	stainless steel Ø5 cm	stainless steel Ø5 cm
ADDITIONAL ELEMENTS	Structural posts protected with welded steel covers; bolts and screws protected with plastic end covers; round head	Structural posts protected with welded steel covers; bolts and screws protected with plastic end covers; round head

Due to constant development of technical solutions and designs made by FreeKids s.c. presented renders may vary from currently produced products. Certificate compliant with safety norms PN-EN 1176:2017