



**LIST OF MODULES**

- 3 x triangular tower
- 2 x square tower
- 2 x gable roof
- 1 x balance beam
- 1 x bridge with railings
- 1 x arch rope-platform bridge
- 1 x suspended bridge
- 1 x climbing entrance
- 1 x rope entrance
- 2 x dragon slide
- 1 x steel lattice wall
- 1 x rope cobweb
- 1 x rope chimney
- 3 x railing W3
- 2 x railing W4

**DANE TECHNICZNE**

- Max. height fall 2,0 m
- Dimensions 9,37 x 9,37 x 3,30 m
- Safety area dimensions 13,0 x 13,0 m
- Safety area 96,5 m<sup>2</sup>
- Recommended surface According to norm 1176-1:2017

**Available options:**

STANDARD		PREMIUM
WOOD	construction elements made of solid wood, impregnated surface ,with square profile 95 x 95 mm	construction elements made of glued-laminated timber, impregnated surface, with square profile 95 x 95 mm
STEEL	galvanized and powder-coated steel elements	galvanized and powder-coated steel elements
PLATES	HPL sheets	HPL and three-coat HDPE panels with milled drawings
SLIDES	stainless steel slide with side-guard panels made of HDPE sheets	stainless steel slide with side-guard panels made of HDPE sheets and three-coat HDPE panels with milled drawings
CHAINS	stainless steel Ø5 cm	stainless steel Ø5 cm
ROPES	ropes made of steel cores wrapped in polypropylene strings, joined by nylon or aluminum connectors	ropes made of steel cores wrapped in polypropylene strings, joined by nylon or aluminum connectors
FOUNDATIONS	The device permanently sited in the ground with C16 / 20 class concrete	The device permanently sited in the ground with C16 / 20 class concrete
ADDITIONAL ELEMENTS	Structural beams connected with clamps. Screw heads, nuts covered with plastic plugs. Cap nuts	Structural beams connected with clamps. Screw heads, nuts covered with plastic plugs. Cap nuts

\* Due to constant development of technical solutions and designs made by FreeKids s.c. presented renders may vary from currently produced products. Certificate compliant with safety norms PN-EN 1176:2017