
Playset Terra 3 Series GALAX GAL-TR3







1107		- B //	201	
LIST	() }-	. 17/16	11 11	II F \
LIJI		IAI		LLJ

4 x square tower
1 x dome roof
1 x slide
1 x climbing wall
2 x stairs
1 x tunnel

1 x rope and platform bridge with barriers

TECHNICAL DATA

Max. height fall (W x L x H) 1,2 m
Dimensions 4,91 x 3,78 x 3,40 m

Safety area dimensions 8,3 x 6,7 m Safety area 44,9 m²

Recommended surface According to norm: 1176-1:2017

Available options:

		PREMIUM	
	STEEL	Galvanized and powder coated steel elements	Structura galvanize
	PLATFORMS	HPL antislip	HPL anti
	PLATES	HDPE / HPL and HDPE plastic panels with three layers and milled drawings	HDPE / H
	SLIDES	Stainless steel slide, side shields made of HDPE	Stainless
F	ROPES	Ropes with a steel core with a braid made of polypropylene, joined by plastic or aluminum connectors	Ropes w by plasti
	FOUNDATIO NS	The device permanently sited in the ground, concrete class C16 / 20	The devi
	ADDITIONAL ELEMENTS	Structural beams covered with steel lids welded to poles. The heads of the screws and nuts covered with plastic plugs. Cap nuts	Structura of the sc

2 x balcony

1 x abacus

3 x barrier

1 x tic tac toe

PREMIUM PLUS
Structural poles of stainless steel, other elements made of galvanized steel with powder coating **
HPL antislip
HDPE / HPL and HDPE plastic panels with three layers and milled drawings.
Stainless steel slide, side shields made of HDPE
Ropes with a steel core with a braid made of polypropylene, joined by plastic or aluminum connectors
The device permanently sited in the ground, concrete class C16 / 20
Structural beams covered with steel lids welded to poles. The heads of the screws and nuts covered with plastic plugs. Cap nuts

^{*} Due to the continuous improvement of technical solutions by FreeKids, presented drawing, including colors and dimensions may slightly differ from currently manufactured devices. Certificate of compliance with the PN-EN 1176: 2017



^{**} Operated execution of stainless steel elements (valuation available on individual request)