

## **LIST OF MODULES**

1x TREEHOUSE 1

1x square tower

1x gable roof

1x rope oblique tunnel

1x slide

1x climbing entrance

1x pole with steps

## **TECHNICAL DATA**

Max. Fall height
Dimensions (L x W x H)
Safety area dimensions

Safety area Recommended surface 1,50 m

7,76 x 2,90 x 4,36 m 9,9 x 5,9

40,80 m<sup>2</sup>

According to the norm 1176-1:2017

## Available options

Availatila tipita		
	PREMIUM	PREMIUM PLUS
STEEL	Galvanized and powder coated steel elements	Structural poles of stainless steel, other elements made of galvanized steel with powder coating **
PLATFORMS	Anti-slip HPL	Anti -slip HPL
PLATES	HPL and three-coat HDPE panels with milled drawings	HPL and three-coat HDPE panels with milled drawings
SLIDES	Stainless steel slide, side shields made of HDPE	Stainless steel slide, side shields made of HDPE
ROPES	Polypropylene ropes with a steel core connected with solid aluminum and plastic connectors	Polypropylene ropes with a steel core connected with solid aluminum and plastic connectors
FOUNDATION	The device permanently sited in the ground with C16 / 20 class concrete	The device permanently sited in the ground with C16 / 20 class concrete $$
ADDITIONAL ELEMENTS	Structural posts protected with welded steel covers; bolts and screws protected with plastic end covers; round head	Structural posts protected with welded steel covers; bolts and screws protected with plastic end covers; round head

<sup>\*</sup> Due to the continuous improvement of technical solutions by FreeKids, presented drywings, including colors and dimensions may slightly differ from turrently manufactured devices. Certificate of compliance with the PN-EN 1176: 2017

1x rope entrance

1x barrier bullseye two-level



<sup>\*</sup> Optional execution of stainless steel elements (valuation available on individual equest)